



RTA15 Series

Features	Benefits																
American made	Many tillers are imported. American made means better parts availability.																
Tractor Horsepower range	17-50 hp (18-37 kW); Dependent upon width and Series of tiller.																
Gearbox warranty	5 Year on housing, gears, seals, and bearings. Shows our confidence in the product.																
Working widths	50", 58", 66" & 74" (127 cm, 147 cm, 168 cm, & 188 cm) to meet customer needs.																
6 1/2" Digging depth	For deep soil penetration.																
Plate steel upper hitch	Plate steel is stronger than flat bar type hitch.																
Clevis hitch	Provides additional strength and easy one person hook-up.																
Hitch sideshift capabilities	Sideshift tiller to cover right tire track. Gearbox slides with tiller.																
Sideshift dimensions	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 33%;"></th> <th style="width: 33%; text-align: center;">Standard</th> <th style="width: 33%; text-align: center;">Maximum Right</th> <th style="width: 33%; text-align: center;">Maximum Left</th> </tr> </thead> <tbody> <tr> <td>58" (147 cm) tiller width</td> <td style="text-align: center;">29"-29" (74.5-74.5 cm)</td> <td style="text-align: center;">12"-46" (30-117 cm)</td> <td style="text-align: center;">35"-23" (89-58 cm)</td> </tr> <tr> <td>66" (168 cm) tiller width</td> <td style="text-align: center;">33"-33" (84-84 cm)</td> <td style="text-align: center;">12"-54" (31-137 cm)</td> <td style="text-align: center;">39"-27" (99-69 cm)</td> </tr> <tr> <td>74" (188 cm) tiller width</td> <td style="text-align: center;">37"-37" (94-94 cm)</td> <td style="text-align: center;">16"-58" (41-147 cm)</td> <td style="text-align: center;">43"-31" (109-79 cm)</td> </tr> </tbody> </table>		Standard	Maximum Right	Maximum Left	58" (147 cm) tiller width	29"-29" (74.5-74.5 cm)	12"-46" (30-117 cm)	35"-23" (89-58 cm)	66" (168 cm) tiller width	33"-33" (84-84 cm)	12"-54" (31-137 cm)	39"-27" (99-69 cm)	74" (188 cm) tiller width	37"-37" (94-94 cm)	16"-58" (41-147 cm)	43"-31" (109-79 cm)
	Standard	Maximum Right	Maximum Left														
58" (147 cm) tiller width	29"-29" (74.5-74.5 cm)	12"-46" (30-117 cm)	35"-23" (89-58 cm)														
66" (168 cm) tiller width	33"-33" (84-84 cm)	12"-54" (31-137 cm)	39"-27" (99-69 cm)														
74" (188 cm) tiller width	37"-37" (94-94 cm)	16"-58" (41-147 cm)	43"-31" (109-79 cm)														
Fits Land Pride Quick Hitch	Allows for quick and easy one person hook-up. Does not offset to the left with Quick Hitch.																
Adjustable Park Stand	Allows for easy hook-up and storage.																
Adjustable Skid Shoes	Control depth with various settings.																
Formed and reinforced rear deflector	Forming gives deflector additional strength. Adjustable deflector allows for various finish results.																
4 'C' Shaped heat-treated tines per flange	'C' Shaped tines require less horsepower to move through the ground.																
RTA1558 1 3/4" Solid steel rotor shaft	Solid steel shaft for strength.																
RTA1566 & RTA1574 2" Solid steel rotor shaft																	
15" (38 cm) Rotor swing diameter	For deep tilling and turning the soil over faster.																
Double lip seal on rotor bearing	Double lip seal helps keep the dirt out and the grease in.																
Cat. 3 heavy-duty fully shielded shear pin or slip-clutch driveline	Protects gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.																
#80 Drive chain enclosed in oil bath	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.																
Stamped chain cover	Stamped forming gives the chain cover strength.																
Fully shielded shear pin or slip-clutch driveline	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.																