

RCR2684 Model

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
5 Year gearbox warranty	A rugged heavy built gearbox capable of handling heavy cutting applications. Shows Land Pride's confidence in gearbox integrity.
130 HP gearbox	A rugged heavy built gearbox capable of handling heavy cutting applications.
Cat. 4 driveline with 4 plate slip-clutch	Excellent gearbox protection with the slip-clutch slipping when encountering obstruction in the blade path. Standard slip-clutch offers convenience over shear-bolts.
Cat. II or III Hitch Quick-Hitch Capability	Permits deck to follow the terrain for an even cut. Quick-Hitch provides for fast hook-up.
Lower clevis type 3-Point hitch	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
84" Cutting width	Wide cutting width, Reduces cutting time in the field.
Heavy 10 gauge deck construction	Can withstand more abuse than lighter gauge decks.
1/4" Side panels for overall reinforcement	Also protects sides from debris being thrown against them from the blades.
Fully welded deck	Robotically welded. Adds additional strength and deck integrity.
Round back design	Allows for more efficient handling and dispersing of material.
10 1/8" Deck Height	Allows cutter to handle heavy cutting conditions.
2" to 12" Cutting height	Provides for a wide range of cutting conditions.
High cutting capacity	Can cut brushy areas with saplings up to 3".
Full length skids with replaceable shoes	Full length skids protect side plate structure, replaceable shoes for convenience.
1/2" x 4" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
Splined blade bar	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
3/16" Oval stump jumper	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
High blade tip speed	Ensures clean cut. (14,369 fpm)
Available with single or dual tailwheels	Dual tailwheels offer greater stability in uneven terrain.
15" Rugged Laminated tailwheel	Laminated material is long lasting in rough conditions. Can't go flat.
Chain or rubber shield option	Located on front and rear. Reduces flying debris.