

606NT COMPACT DRILL

HP REQUIRED
40 HP Min.

HITCH
Pull-Type




COMPACT DRILLS

End wheel efficiency.

The 6' Pull-type No-Till Drill (606NT) features an end wheel design that reduces side-loading on openers when operated on contours and curves, eliminating premature opener wear.

With the optional native grass and small seeds box this machine is quite capable in pasture renovations and food plot seeding. Other features like heavy duty coulters, calibration crank, central grease bank, lock-out hubs for transport, and optional weight brackets create a system designed for long-term dependability and productivity in a broad range of seeding applications.

	606NT
Horsepower	40 HP Min.
Hitch	Pull-Type
Primary Design	End Wheel No-Till
Row Spacings	7-1/2"
Number of Openers	9
Tire Size	7.00-15LT
Weight - lbs (kg)	2,700 (1,124)
Working Width	6'
Width	8'6"
Transport Length	11'5"
Transport Clearance	14"
Transport Height	5'1"
Opener Series	06 Series
Opener Travel	6-1/2"
Opener Depth Range	0 - 3-1/2"
Opener Down Pressure - lbs	90-180
Coulter	5/8" Turbo or 5/16" Fluted
Coulter Pre-Load - lbs	450
Main Box Capacity	12 bu.
Small Seed Box	1.44 bu.
Native Grass Box	6 bu.
Color	



06 SERIES

5/8" Turbo Blade for maximum penetration or 5/16" Fluted Blade for pasture renovation and low soil disturbance.



Exclusive fluted wide seed cup delivers outstanding accuracy; delivering the rate you choose, evenly and gently.

4-Speed gearbox provides increased accuracy and flexibility of the metering system by giving the operator more choices for drive speed.

