

	800
Hitch	Pull-Type
Primary Design	End Wheel Min-Till
Row Spacings	6", 7-1/2"
Number of Openers	15 - 6" spacing, 12 - 7-1/2" spacing
Tire Size	700-15LT
HP Requirements (min)	45 HP
Weight - lbs (kg)	2,379 (1,079)
Working Width	7'6"
Width	9'8-1/2"
Transport Length	12'
Transport Clearance	9"
Transport Height	5'4"
Opener Series	00 Series
Opener Travel	6.5"
Opener Depth Range	0 - 3-1/2"
Opener Down Pressure - lbs	90-180
Main Box Capacity	16 bu.
Small Seed Box	2 bu.

Big Performance in a Small Package.

This 8' Min-Till Drill (800) uses the field proven 00 series opener to properly place seed. This rugged opener utilizes 13-1/2" 4mm thick disk blades, full length seed tube and an 18 position T-handle press wheel to precisely control seed depth. Changing the 5-position, centrally located opener down pressure adjustment is quick and easy, ensuring the correct down pressure regardless of the conditions.

Other features include a 1-3/4" fluted feed metering system. It utilizes a 4-speed gear box and adjustable gate opening to accurately set a wide variety of planting rates for crops from alfalfa to peas. You may also add a dry fertilizer and/or a small seeds attachment to tailor the drill to your needs.

Other features include a lock-out hub to free wheel the drive system during transport. Safety lighting, electronic acre meter, lift cylinder with hoses, calibration crank, "V" bottom dividers for easy clean out, and folding tongue are all standard equipment. An optional seed box agitator is available.



Color: 



DIGITAL ACREMETERS - LED readout of current acres on machine. Unique design conserves battery power.



SAFETY LIGHTS - LED lights provide high visibility and safety during transport.



LOCK OUT HUBS - Disengages all drive components for transport reducing wear and tear.



Choice of 2x13 Single Press heels or 3x13 Center Rib Press Wheels

