

## Appendix A - Reference Information

### Specifications and Capacities

Drill Model	3P606NT820975	606NT820975
Row Count	9	9
Row Spacing	7.5 in. (19.1 cm)	7.5 in. (19.1 cm)
Swath	67.5 in. (171.5 cm)	67.5 in. (171.5 cm)
Transport Width	6 ft. 1/2 in. (72.5 in., 184.2 cm)	8 ft 10 in. (106.0 in., 269.2 cm)
Length	5 ft 1 in. (61.0 in., 154.9 cm)	11 ft 5 in. (137.0 in., 348.0 cm)
Working Height	5 ft 1 in. (61.0 in., 154.9 cm)	5 ft 1 in. (61.0 in., 154.9 cm)
Transport Clearance	Depends on tractor hitch	14.0 in. (35.6 cm)
Weight, Maximum, Empty <sup>1</sup>	2280 lbs. (1034 kg)	2700 lbs. (1225 kg)
Weight, Maximum, Full	4230 lbs. (1919 kg)	4600 lbs. (2087 kg)
Main Seed Box Capacity	12 bu. (423 litre)	12 bu. (423 litre)
Native Grass Box Capacity	6 bu. (211 litre)	6 bu. (211 litre)
Small Seeds Box Capacity	1 bu. (51 litre)	1 bu. (51 litre)
Seed Box Agitator	Optional in Main Seed box, Standard in Native Grass box	
Min. Tractor HP Req. <sup>2</sup>	60 hp (45 Kw)	40 hp (30 Kw)
Hitch Type	Category II	Clevis or Pintle
Hydraulic Circuits Req.	None	1
Tire Size	5.70L x 8 Lug Type	7.00-15 LT
Operating Depth	0 to 3.5 in. (0 to 8.9 cm)	0 to 3.5 in. (0 to 8.9 cm)

1. See "Transporting" topic for typical weights of various configurations.

2. Power requirements vary significantly with conditions and practices.

32774B

### Tire Pressures

Tire Size	Inflation
5.70L-8 Lug Type, 715 lb (324 kg) load rating	50 psi 345 kPa
7.00-15 LT 2040 lb (925 kg) load rating	60 psi 414 kPa

### Tire Warranty Information

All tires are warranted by the original manufacturer of the tire. Tire warranty information is found online at the manufacturer's websites listed below. For assistance or information, contact your nearest Authorized Farm Tire Retailer.

Manufacturer	Website
Firestone	<a href="http://www.firestoneag.com">www.firestoneag.com</a>
Gleason	<a href="http://www.gleasonwheel.com">www.gleasonwheel.com</a>
Titan	<a href="http://www.titan-intl.com">www.titan-intl.com</a>