

AP-PS2072 & AP-PS2086

Specifications & Capacities		
Model Nos.	AP-PS2072	AP-PS2086
Tractor Horsepower*	25-60 (18.6-44.7 kW) (Not meant for small tractors such as Kubota BX)	
Seeding Width (Broadcast)	72" (1.83 m)	86" (2.18 m)
Overall Width	81" (2.06 m)	95" (2.41 m)
Overall Height	42" (1.07 m)	
Overall Length	35" (88.9 cm)	
Empty Weight	1464 lbs (664.1 kg)	1677 lbs (760.7 kg)
Seedbox Capacity	1 Bushel/Foot (35.2 L / .39 m)	
3-Point Tractor Hitch	Category 1; Quick Hitch Adaptable	
Main Seedbox Construction	Continuous welded for water tight construction	
Lid construction	Heavy duty precision fit with seed splash guard	
Ground Drive Metering	Driven from right side of rear roller with #40 Roller chain	
Seed Cup Drive	Chain driven from right side of rear roller	
Seed Cup Agitation	Chain driven star type agitators above seed cups	
Seed Cups (Patent Pending) Bi-directional Fluted Cups for Accurate metering	10	12
Seed Settings	Wide range of calibration	
Seed Drop	Wind guarded	
Track Removers	Double torsion spring height adjustable and replaceable two each	
9" (22.9 cm) Notched Cast Iron Bed Forming Packer Rollers. (Front)	31	37
9" (22.9 cm) Notched Cast Iron Bed Forming Packer Rollers. (Rear)	30	36
Roller Spindles	1 3/4" with greasable bearings	

*The Primary Seeder is not meant for a Kubota BX tractor or comparable frame tractors.

