

	MEDIUM-DUTY				HEAVY-DUTY
	RC2512	RC2515	RC(G)3715	RC3620	RC(G)3712
Horsepower	40-100 HP	50-100 HP	50-160 HP	70-160 HP	50-160 HP
Hitch	Pull-Type; Standard Clevis, LP Performance Self-Leveling	Pull-Type; Self Leveling Hitch & Clevis	Pull-Type; Standard Swivel Clevis, LP Performance Self-Leveling, Ball, Pintle, or Bar-Tite Hitch	Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite	Pull-Type; Standard Swivel Clevis, LP Performance Self-Leveling, Ball, Pintle, or Bar-Tite Hitch
Working Width (cm)	12' (366)	15' (457)	15' (457)	20' (607)	12' (366)
Overall Width	12'7"	15'7"	15'10"	20' 10"	12'10"
Min. Transport Width	7'11"	8'4"	10'3"; 7'3" w/Narrow Option	9' 11"	9' 4"
Overall Length	13'3"	15'6"	16'3"	17' 6"	15'3"
Machine Weight - lb (kg)	2,540 (1152)	3,202 (1,452)	4,380 (1,987)	6,680 (3,030)	3,730 (6,192)
Cutting Height	1-1/2" - 12"	2" - 13"	1-1/2" - 16" **	2" - 12" **	1-1/2" - 14" **
Cutting Capacity	1-1/2" Diameter	1-1/2" Diameter	3" Diameter	2" Diameter	3" Diameter
Tongue Weight - lb	793	1,022	1,594	1,750	1,240
Max. Turning Angle	80° with CV	80° with CV	80° with CV	80° with CV	80° with CV
Deck Height	11"	11-1/4"	12"	13"	11"
Deck Thickness	10 Gauge	10 Gauge	10 Gauge	10 Gauge	10 Gauge
Deck Shock Protection	Spring Cushioned	Spring Cushioned	Spring Cushioned Center Axle	Spring Cushioned	Spring Cushioned Center Axle
Deck Rings	N/A	N/A	Optional	Optional	N/A
Side Panel Thickness	3/16"	1/4"	1/4"	1/4"	1/4"
Chain Guards Front & Rear	Standard	Standard	Double Optional	Double Optional	Double Optional
Skid Shoes	Wings & Center, Replaceable	Wings & Center, Replaceable	Wings & Center, Replaceable, Beveled	Wings & Center, Replaceable	Wings & Center, Replaceable, Beveled
Blades	1/2" x 3" Uplift	1/2" x 4" Uplift	1/2" x 4" Uplift	1/2" x 4" High Lift	1/2" x 4" Uplift
Blade Bolt	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut
Blade Tip Speed (Feet per minute)	540 Center	16,500 fpm,	15,000 fpm	15,268 fpm	16,000 fpm
	Wings	16,000 fpm	15,000 fpm	15,000 fpm	16,000 fpm
	1000 Center	-	-	15,768 fpm	16,500 fpm
	Wings	-	-	14,620 fpm	16,500 fpm
Blade Overlap	6"	6"	6"	6"	6"
Dishpan	10 Gauge, Round, Dish Shaped with 1" x 3-1/2" Blade Bar	10 Gauge, Round, Dish Shaped with 1" x 4" Blade Bar	3/16" Round, Round, Dish Shaped	10 Gauge Round, Dish Shaped w/ 1" x 4-1/2" Blade Bar	10 Gauge Round, Dish Shaped w/ 1" x 4-1/2" Blade Bar
Hydraulics	Wings	2" x 8"	2-1/2" x 10"	2-1/2" x 12"	3" x 12"
	Center	2-1/2" x 8"	2-1/2" x 8"	3" x 8"	Rephasing Cylinders
Gearbox Rating^A	540 RPM: 160 HP Divider; 100 HP Center & Wings	540 RPM: 160 HP Divider; 100 HP Center & Wings	540 or 1000 RPM: 160 HP Divider; 130 HP Center & Wings	540 or 1000 RPM: 250 HP Divider, 150 HP Ctr & Wings	540 or 1000 RPM: 160 HP Divider; 130 HP Center & Wings
Gearbox Output Shaft	1-1/2"	1-5/8"	2"	2"	2"
Gearbox Input Shaft	1-3/8" 6 Spline	1-3/8" 6 Spline	1-3/4" 20 Spline	1-3/4" 20 Spline	1-3/4" 20 Spline
Input Driveline	Cat. 4 CV	Cat. 4 CV	Cat. 6 CV	Cat. 6 CV	Cat. 6 CV
Connecting Drivelines	Cat. 3 Slip-Clutch	Cat. 3 Slip-Clutch	Cat. 4 Slip-Clutch	Cat. 4 Slip-Clutch	Cat. 4 Slip-Clutch
Tires	21" Laminated Tires 20.5" Aircraft Tires	21" Laminated Tires 29" Aircraft Tires	21" Laminated 29" Used Aircraft 25.5" New 20-Ply Pneumatic or Foam-Filled	21" Laminated 29" Used Aircraft 27" Foam-Filled	21" or 26" Laminated 29" Used Aircraft 25.5" Aircraft, Pneumatic or Foam-Filled
Transport Lights	Standard	Standard	Standard	Standard	Standard
Color Options					
Limited Gearbox Warranty[*]					

	HEAVY-DUTY				EXTRA HEAVY-DUTY
	RC(G)4715	RC5615	RC4620	RC5020	RC6615 / RCB6615
Horsepower	50-250 HP	50-250 HP	70-250 HP	70-250 HP	50-250 HP
Hitch	Pull-Type; Standard Swivel Clevis, LP Performance Self-Leveling, Ball, Pintle, or Bar-Tite Hitch	Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite	Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite	Pull-Type; Standard Clevis, Swivel, Ball, Pintle, or Bar-Tite Hitch	Pull-Type; Standard Clevis, LP Performance Self-Leveling, Pintle, Ball, Bar-Tite
Working Width (cm)	15' (457)	15' (457)	20' (607)	20' (607)	15' (457)
Overall Width	15' 10"	15' 8"	20' 10"	20' 9-1/2"	15' 8"
Min. Transport Width	10'3"; 7'3" w/Narrow option	9' 1"	9' 11"	8' 9"	9' 1"
Overall Length	16'3"	16'	17' 6"	19' 3"	16'
Machine Weight - lb (kg)	4,700 (2,132)	5,446 (2,470)	6,540 (2,966)	6,528 (2,961)	RC66: 5,660 (2,567); RCB66: 5,738 (2,603)
Cutting Height	1-1/2" - 16"	2" - 14"	2" - 12" **	2" - 14" **	2" - 14"
Cutting Capacity	4" Diameter	4" Diameter	3" Diameter	3" Diameter	4-1/2" Diameter
Tongue Weight - lb	1,700	1,860	2,160	2,300	RC66: 1,860; RCB66: 1,842
Max. Turning Angle	80° with CV	80° with CV	80° with CV	80° with CV	80° with CV
Deck Height	12"	12"	13"	10-1/2"	12"
Deck Thickness	10 Gauge	7 Gauge Bottom; 10 Gauge Top	10 Gauge	10 Gauge	7 Gauge Bottom, 10 Gauge Top
Deck Shock Protection	Independent Wheel Arm Springs	Independent Wheel Arm Springs	Spring Cushioned Center Axle	Spring Cushioned Center Axle	Independent Wheel Arm Springs
Deck Rings	Optional	Optional	Optional	Optional	Optional
Side Panel Thickness	1/4"	1/4" Replaceable	1/4"	1/4"	1/4" Replaceable
Chain Guards Front & Rear	Double Optional	Double Optional	Double Optional	Double Optional	Double Optional, Double w/Cable Optional
Skid Shoes	Wings and Center, Replaceable, Beveled	Wings and Center, Replaceable, Beveled	Wings and Center, Replaceable, Beveled	Wings and Center, Reversible, Replaceable, Beveled	2 on Center Section, Replaceable, Beveled RC66: 1 Ea. Wing; RCB66: 2 Ea. Wing
Blades	1/2" x 4" Uplift	1/2" x 4" Uplift	1/2" x 4" High Lift	1/2" x 4" High Lift	1/2" x 4" Uplift
Blade Bolt	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut	Keyed with Hardened Flatwasher & Lock Nut
Blade Tip Speed (Feet per minute)	540 Center	16,300 fpm	16,300 fpm	17,000 fpm	17,377 fpm
	Wings	16,300 fpm	16,300 fpm	17,000 fpm	17,329 fpm
	1000 Center	16,300 fpm	16,300 fpm	18,000 fpm	18,165 fpm
	Wings	16,000 fpm	16,000 fpm	18,000 fpm	18,317 fpm
Blade Overlap	6"	6"	6"	6"	6"
Dishpan	Forged Diamond Blade Bar; Optional 3/16" Round Dishpan	3/16", Round, Dish Shaped with 1" x 5" Blade Bar	1" Plate Diamond Blade Bar; Optional 3/16" Round Dishpan	3/16" Round, Dish Shaped w/ 1" Steel Plate Support	3/16" Round, Dish Shaped RC66: 1" x 5" Blade Bar RCB66: 1" Steel Plate Support
Hydraulics	Wings	2-1/2" x 12"	3" x 8"	3" x 12"	3" x 8"
	Center	3" x 8"	3-1/2" x 8"	Rephasing Cylinders	4" x 8"
Gearbox Rating^A	540 or 1000 RPM: 250 HP Divider, 210 HP Center & Wings	540 or 1000 RPM: 250 HP Divider, 210 HP Center & Wings	540 or 1000 RPM: 250 HP Splitter, 210 HP Center & Wings	540 or 1000 RPM: 250 HP Divider, 225 HP Center & Wings	540 or 1000 RPM: 250 HP Divider, 225 HP Center & Wings
Gearbox Output Shaft	2-3/8"	2-3/8"	2-3/8"	2-3/8"	2-3/8"
Gearbox Input Shaft	1-3/4" 20 Spline	1-3/4" 20 Spline	1-3/4" 20 Spline	1-3/4" 20 Spline	1-3/4" 20 Spline
Input Driveline	Cat. 6 CV	Cat. 6 CV	Cat. 6 CV	Cat. 6 CV	Cat. 6 CV
Connecting Drivelines	Cat. 4 or Cat. 5 Slip-Clutch	Cat. 4 or Cat. 5 Slip-Clutch	Cat. 5 Slip-Clutch	Cat. 5 Slip-Clutch	Cat. 5 Slip-Clutch
Tires	21" or 26" Laminated 29" Used Aircraft 24" Foam-Filled	21" Laminated 29" Used Aircraft 25.5" Foam-Filled	21" Laminated 29" Used Aircraft 27" Foam-Filled	21" Laminated 29" Used Aircraft 27" Foam-Filled	21" Laminated 29" Used Aircraft 25.5" Foam-Filled
Transport Lights	Standard	Standard	Standard	Standard	Standard
Color Options					
Limited Gearbox Warranty[*]					

