






	RTR0542	RTR0550	RGA1242 RGR1242	RGA1250 RGR1250	RGA1258 RGR1258	RGA1266 RGR1266	RGA1274 RGR1274	RGA1282 RGR1282	RTA1242 RTR1242	RTA1250 RTR1250	RTA1258 RTR1258	RTA1266 RTR1266	RTA1274 RTR1274	RTA1282 RTR1282	RTA1558 RTR1558	RTA1566 RTR1566	RTA1574 RTR1574	RTA2562	RTA2570	RTA3576
Horsepower	Up to 26 HP		18-60 HP		23-60 HP		30-60 HP	35-60 HP	15-40 HP		20-50 HP		25-60 HP	30-60 HP	17-50 HP			25-75 HP		35-95 HP
Hitch	Cat. 1		Cat. 1						Cat. 1						Cat. 1			Cat. 1 & 2		
Width-Endplate to Endplate (cm)	42" (107)	50" (127)	42" (107)	50" (127)	58" (147)	66" (168)	74" (188)	82" (208)	42" (107)	50" (127)	58" (147)	66" (168)	74" (188)	82" (208)	58" (147)	66" (168)	74" (188)	64" (162)	70" (178)	76" (193)
Overall Width RGA RGR	46-1/2" (118)	54-1/2" (139)	47-1/8" (47-1/2")	55-1/8" (55-1/2")	63-1/8" (63-1/2")	71-1/8" (71-1/2")	79-1/8" (79-1/2")	87-1/8" (87-1/2")	47-3/8" (48-1/4")	55-3/8" (56-1/4")	63-3/8" (64-1/4")	71-3/8" (72-1/4")	79-3/8" (80-1/4")	87-1/8" (87-1/4")	64-1/4"	72-1/4"	80-1/4"	68"	76"	81-1/2"
Weight - lb (kg) RGA RGR	268 (122)	298 (135)	458 (208) 462 (210)	493 (224) 497 (225)	526 (239) 530 (240)	562 (255) 567 (257)	596 (270) 601 (273)	647 (293) 653 (296)	391 (177) 404 (183)	421 (191) 435 (197)	448 (203) 463 (210)	476 (216) 493 (224)	503 (228) 521 (236)	552 (250) 581 (264)	444 (201)	476 (216)	508 (230)	649 (294)	663 (301)	856 (388)
Number of Flanges	6	7	5	6	7	8	9	10	5	6	7	8	9	10	7	8	9	8	9	8
No. of Blades per Flange	4 C-Shape		6 "C" Shaped Blades per Flange						4 C-Shape						4 C-Shape			6 C-Shape		6 C-Shape
Blade Spacing	6-1/2"	6-3/4"							7-7/8"						7-7/8"			7-7/8"		9"
Max. Tilling Depth^	6-1/2"		7"						6-1/2"						6-1/2"			7"		7"
Skid Shoe Settings	4		Adjustable						7						7			6		6
Rotor Swing Diameter	13"		17"						15"						15"			17"		19"
Rotor Shaft Speed	230 rpm at 540 rpm PTO		211 rpm at 540 rpm PTO						211 rpm at 540 rpm PTO						211 rpm at 540 rpm PTO			220 rpm at 540 rpm PTO		204 rpm at 540 rpm PTO
PTO Driveline			Cat 4 Slip Clutch						Cat 3 Slip Clutch						Category 3, Off-Center Shear Bolt or Slip Clutch			Cat 3 Heavy Duty Shear Bolt or Slip Clutch		Cat 4 Slip Clutch
Gearbox			60 HP, 540 rpm, Cast Iron Housing, Drain Plug						60 HP, 540 rpm, Cast Iron Housing, Drain Plug						50 HP, 540 rpm, Cast Iron Housing, Drain Plug			55 HP, 540 rpm, Cast Iron Housing, Drain Plug		75 HP 540 rpm, Cast Iron Housing, Drain Plug
Drive Chain	#80 High Tensile in Oil Bath								#80 High Tensile in Oil Bath						#80 High Tensile in Oil Bath			#100 High Tensile in Oil Bath		#100 High Tensile in Oil Bath
Drive End Construction			Spur Gears Enclosed in Oil Bath with Oil Level Plug or Sight Glass and Oil Fill/Breather Plug																	
Sprockets	Hardened Teeth, Splined Center		Hardened Teeth, Splined Center						Hardened Teeth, Splined Center						Hardened Teeth, Splined Center			Hardened Teeth, Splined Center		Hardened Teeth, Splined Center
Colors																				

	RTA2064	RTA2072	RTR2064	RTR2072	RTR2570
Horsepower	23-75 HP				25-75 HP
Hitch	Cat. 1				Cat. 1
Width-Endplate to Endplate (cm)	64" (162)	72" (183)	64" (162)	72" (183)	70" (178)
Overall Width	70-13/16"	77-7/8"	70-13/16"	77-7/8"	76" (193)
Weight - lb (kg)	689 (313)	734 (333)	748 (339)	795 (361)	868 (394)
Number of Flanges	8	9	8	9	9
No. of Blades per Flange	6 C-Shape				6 C-Shape
Blade Spacing	7-1/2"				7-7/8"
Max. Tilling Depth^	7"				7"
Skid Shoe Settings	7				7
Offset	14"	18"	14"	18"	Up to 5"
Number of Sifting Tines	N/A		43	48	46
Rotor Swing Diameter	17"				17"
Rotor Shaft Speed	220 rpm at 540 rpm PTO				220 rpm at 540 rpm PTO
PTO Driveline	Cat 3, Heavy Duty Shear Bolt or Slip Clutch				Cat 3 Slip Clutch
Gearbox	50 HP, 540 rpm, Cast Iron Housing, Drain Plug		55 HP, 540 rpm, Cast Iron Housing, Drain Plug		
Drive Chain	#80 High Tensile in Oil Bath				#100 High Tensile in Oil Bath
Sprockets	Hardened Teeth, Splined Center				Hardened Teeth, Splined Center
Colors	